

DESCRIPTION

CODE

33-83 l/min 230 VAC



EA-30

EA-30 (1.49 kW) 230/400 VAC TRIPHASE - 33 l/min - 1"

11
bar

24130

- Maximum suction height: 3 m
- Flow: 33 l/min
- Motor: 1.49 kW 230/400 VAC Triphase - IP-55 protection
- Consumption: 5.3 / 3.1 A
- 1,500 rpm
- Max. pressure: 11 bar (adjustable through the bypass valve)
- Max. working temperature: 130 °C
- Suction/delivery pump diameter: 1" GAS (BSP)



EA-50

EA-50 (1.49 kW) 230/400 VAC TRIPHASE - 50 l/min - 1 1/4"

8
bar

24150

- Maximum suction height: 4 m
- Flow: 50 l/min
- Motor: 1.49 kW 230/400 VAC Triphase - IP-55 protection
- Consumption: 9.9 / 5.7 A
- 1,500 rpm
- Max. pressure: 8 bar (adjustable through the bypass valve)
- Max. working temperature: 180° C
- Suction/delivery pump diameter: 1 1/4" GAS (BSP)



EA-80

EA-80 (2.98 kW) 230/400 VAC TRIPHASE - 83 l/min - 1 1/4"

10
bar

24160

- Maximum suction height: 4 m
- Flow: 83 l/min
- Motor: 2.98 kW 230/400 VAC Triphase - IP-55 protection
- 1,500 rpm
- Max. pressure: 10 bar
- Max. working temperature: 180 °C
- Suction/delivery pump diameter: 1 1/4" GAS (BSP)

5
bar

BEA-100

- Maximum suction height: 3-4 m
- IP-55 protection
- Consumption: 31 A
- 1,500 rpm
- Max. pressure: 5 bar (adjustable through the bypass valve)
- Max. working temperature: 180 °C

BEA-100 230/400 VAC - 115 l/min - 1 1/4"

24170



BEA-150

BEA-150 400/660 VAC - 175 l/min - 1 1/2"

24180



BEA-1000

BEA-330 400/660 VAC - 330 l/min

24191

BEA-1000 400/660 VAC - 1000 l/min

24200

Ask for other flows.